


Collecta ScreedBoard 28 laid on timber sub-floor
Solid timber joists
Use with timber frame walls only



Floating floor treatment	Collecta ScreedBoard 28 (See Table TF10 for full details)
Floor decking	15mm thick (min) OSB
Joists	220mm (min) solid timber joists
Absorbing material	100mm (min) quilt insulation (10-36g/m ³) between joists
Ceiling	See Table TF10 for ceiling treatment



FASTRACKCAD[®]
ARCHITECTURAL CAD DATABASES

Fig. TF10

Table TF10


PCT floating floor treatment	Perimeter resilient flanking strip required	Ceiling treatment						
<p>ScreedBoard[®] 28 0 GWP</p> <p>High density composite resilient overlay treatment</p> <p>Additional layers required to complete treatment</p> <ul style="list-style-type: none"> Mineral wool quilt laid between joists - 100mm (min) 10-33kg/m³ <p>No need for screws Interlocking edges glued together with Collecta SB joint adhesive</p> <p>Product information Board dimensions: 28mm x 600mm x 1200mm Edge profile: Interlocking tongue & groove Weight: 26.00kg/m² / 18.72kg per board Collecta SB joint adhesive: 1L for every 33m² of boards</p> <p>Typical PCT performance⁽²⁾</p> $D_{nT,w} + C_{tr} = 50\text{dB}$ $L_{nT,w} = 50\text{dB}$ <p>Code credits*</p> <table border="1"> <tr> <td>Mat 1</td> <td>Pol 1</td> <td>Hea 2</td> </tr> <tr> <td>2</td> <td>1</td> <td>3</td> </tr> </table> <p>Benefits of ScreedBoard 28 over an acoustic batten system (FFT1)</p> <ul style="list-style-type: none"> Grey dry screed finish Only 28mm thick Reduces number of brick courses required Able to accept ceramic tiles Only one component to install (+ edge strip) Interconnecting edge detail - no screws req'd Weighs only 18.72kg per board (0.72m²) Same weight/m² as FFT1 treatment No need to employ a specialist contractor 	Mat 1	Pol 1	Hea 2	2	1	3	<p>YELOfon[®] FS50</p> <p>Pre-formed polyethylene foam flanking angle: 6mm x 50mm x 30mm x 2m placed around the perimeter of the flooring board to isolate floor from walls and skirting.</p>	<p>Ceiling board fixings must not penetrate or touch the floor joists 16mm (min) metal resilient bars mounted at right angles to the joist at 400mm centres.</p> <p>Primary ceiling: CT1-Two layers of gypsum-based board, composed of 19mm (nominal 13.5kg/m²) fixed with 32mm screws and 12.5mm (nominal 10kg/m²) fixed with 42mm screws, with all joists staggered. CT2-Two layers of gypsum-based board, composed of 15mm (nominal 12.5kg/m²) fixed with 25mm screws and a second layer of 15mm (nominal 12.5kg/m²) fixed with 42mm screws, with all joists staggered.</p> <p>Sacrificial ceiling: Metal ceiling system with a 100mm (min) void fixed to underside of primary ceiling. One layer of nominal 8kg/m² gypsum based board.</p>
Mat 1	Pol 1	Hea 2						
2	1	3						

* Code for Sustainable Homes (CSH) credits quoted are typical. Mat 1 value taken from the BRE Green Guide. Pol 1 credit is only awarded if all the other insulation products used have a GWP of <5. Hea 2 credits are based on the floor being pre-completion tested and the separating wall performing to at least the same acoustic standard. Credits subject to relevant category weighted value. See page 5 for further information.


Acoustic values
⁽²⁾ Values quoted are typical, based on the treatment being installed correctly and pre-completion tested.
Airborne performance tested in accordance with BS EN ISO 140-4:1998
Impact performance tested in accordance with BS EN ISO 140-7: 1998

Design & installation details - *Collecta* ScreedBoard® 28

The acoustic performance of the floor structure will be compromised if the ScreedBoard 28 is not completely isolated from the timber sub-floor, soil pipes, door frames, surrounding walls and their treatments. To address this risk, each potential problem area needs to be detailed accordingly.




Fixing tools




A. Club hammer
 B. Hand or skill saw
 C. ScreedBoard® "Pull bar"
 D. ScreedBoard® "Fixing batten"
 E. ScreedBoard® adhesive
 Packing shims (not shown)

1 Door threshold




Leave a 5-10mm expansion gap between the habitable area and the communal area ScreedBoards.

2 Metal frame partition built off the floor treatment




Non-load bearing metal frame or timber stud walls can be built directly off the ScreedBoard 28. Care should be taken to ensure screws DO NOT penetrate the resilient layer.

3 Timber stud partition built off the floor treatment




4 Baths, shower trays and sanitary ware built off floor treatment.




Baths, shower trays and sanitary ware can be built directly off the ScreedBoard 28. Under no circumstance should screws penetrate the resilient layer.

5 Baths, shower trays and sanitary ware built off the structural floor




Baths, shower trays and sanitary ware built off the structural floor should be isolated from the ScreedBoard 28 and any floor finished.

6 Metal frame partition built off the structural floor




Lightweight partition walls built off the structural floor **MUST** be isolated from the ScreedBoard with YELOfon FS50 strip.

7 Wall treatment installed before the ScreedBoard 28




Wall treatments **MUST** be isolated from the ScreedBoard 28 with YELOfon FS50 strip.

8 Wall treatment installed after the ScreedBoard 28



Wall treatments **MUST** be isolated from the ScreedBoard 28 with YELOfon FS50 strip.

9 Timber stud partition built off the structural floor



Lightweight Internal walls built off the structural floor **MUST** be isolated from the ScreedBoard with YELOfon FS strip.